

Innlights

Innlights^{TC}
Displaysolutions

TRAILER-BESPIELUNG
VIA SMARTPHONE
MIT DER INNLIGHTS RCA

InnScreen TRAILER C5

[PIXEL PITCH 5,9 mm] Outdoor

// 15 m² hochauflösender
LED Videotrailer

Mobiler LED-Screen [5 x 3 m],
einsatzbereit in 30 Minuten.

Hydraulischer Teleskopträger
mit automatischer
Screen-Drehung um 310°.



SCREEN SIZE LxH [m]	5 x 3
SCREEN RESOLUTION [px]	840 x 504
TOTAL HEIGHT [m]	6,10



Innlights^{TC} Displaysolutions

InnScreen C5 Trailer

PHYSICAL FACTS INNSCREEN C5

PIXEL PITCH [mm]	5,95
BRIGHTNESS [cd/m ²]	4.500
PROTECTION LEVEL [Front/Back]	IP 65
CABINET WEIGHT [kg]	8
CABINET SIZE (WxH) [mm]	500 x 500 x 75
CABINET RESOLUTION [px]	84 x 84
PIXEL DENSITY [px/m ²]	28.224
CABINET MATERIAL	Aluminum CNC finish

PHYSICAL FACTS TRAILER

TRAILER SIZE L x W x H [m]	5,60 x 2,10 x 2,25
TOTAL HEIGHT [m]	6,10
TOTAL WEIGHT [kg]	2.800
SCREEN SIZE L x H [m]	5 x 3
SCREEN RESOLUTION [px]	840 x 504

INNLIGHTS STANDARDS

Nationstar High Brightness SMD (Outdoor Series)
Power Sockets: Neutrik Powercon True1 (IP65 outdoor)
Power Cables: Titanex Ho7RN-F 3G2.5
Data Sockets: Neutrik CAT6a NE8FDX-Y6-W
Data Cables: NE8MX6 (IP65 outdoor) with 0,5m CAT7 PUR AWG26
High Class Connex Power Distributor
Professional Image Processing / Video Direction
Certificates: ROHS, CE (EMV Klasse B), TÜV Rheinland, BGVA ₃

OPTICAL FACTS

VIEWING ANGLE HOR/VER [Deg]	140 / 140
REFRESH RATE MIN. [Hz]	1.920
IC DRIVER	MBI 5124
LED TYPE	SMD 3535
LED	Nationstar
PROCESSING [bit]	16
VIDEO PROCESSING	Novastar A4+

POWER SUPPLY

INPUT VOLTAGE [V]	110 - 240
WATTAGE MAX./AVG. [W /Cabinet]	138 / 45
WATTAGE MAX./AVG. [W /m ²]	552 / 180
WATTAGE MAX./AVG. [W /15 m ²]	8.280 / 2.700

ENVIRONMENT

OPERATION HUMIDITY [RH]	10% - 90%
WORKING TEMP. MIN./MAX. [°C]	-30 / +40