

Innlights

Innlights^{TC}
Displaysolutions

InnScreen C2

[PIXEL PITCH 2,84 mm] Indoor

// High Standards.
Best Performance.

Ultimate image experience designed for
best stage rental performance.



FACTS [m²]

BRIGHTNESS [cd/m ²]	1.100
WEIGHT [kg/m ²]	36
RESOLUTION [pixel/m ²]	352 x 352
CABINETS PER m ²	4
WATTAGE MAX./AVG. [W/m ²]	736 / 296



Innlights^{TC}

Displaysolutions

InnScreen C2

PHYSICAL FACTS

PIXEL PITCH [mm]	2,84
BRIGHTNESS [cd/m ²]	1.100
PROTECTION LEVEL [Front/Back]	IP 21 / IP 43
CABINET WEIGHT [kg]	9
CABINET SIZE [mm]	500 x 500 x 75
CABINET RESOLUTION [px]	176 x 176
PIXEL DENSITY [px/m ²]	123.904
CABINET MATERIAL	Aluminum CNC finish

ACCESSORIES

CABINET CASE SIZE (LxWxH) [cm]	105 x 58 x 75
CABINET CASE WEIGHT (full) [kg]	114
CABINETS PER CASE	8
m ² PER CASE	2
HANGING BRACKETS	Single / Double

EASYFRAME-SYSTEM FOR STACKED INSTALLATIONS

INNLIGHTS STANDARDS

Black Face LED (Indoor Series)
Professional Image Processing / Video Direction
Certificates: CE (EMV), RoHs

OPTICAL FACTS

VIEWING ANGLE HOR/VER [Deg]	140 / 140
REFRESH RATE MIN. [Hz]	3.840
IC DRIVER	MBI 5153
LED TYPE	SMD 2020 (black face)
LED	Nationstar
PROCESSING [bit]	15
VIDEO PROCESSING	Novastar

POWER SUPPLY

INPUT VOLTAGE [V]	110 - 220
WATTAGE MAX./AVG. [W /Cabinet]	184 / 74
WATTAGE MAX./AVG. [W /m ²]	736 / 296
CABINETS PER 16 A PHASE	16

ENVIRONMENT

OPERATION HUMIDITY [RH]	10% - 90%
WORKING TEMP. MIN./MAX. [°C]	-20 / +60