


Innlights

Innlights^{TC} Displaysolutions



InnScreen C3

[PIXEL PITCH 3,9 mm] Indoor

// High Performance.
Straight & Curved Design.

Ultimate image experience paired with the impressive effect of a combinable straight and curved screen.

FAST & EASY INSTALLATION

/ STRAIGHT

/ CONVEX (1° - 20°)

/ CONCAVE (1° - 30°)



FACTS [m²]

BRIGHTNESS [cd/m ²]	1.200
WEIGHT [kg/m ²]	36
RESOLUTION [pixel/m ²]	256 x 256
CABINETS PER m ²	4
WATTAGE MAX./AVG. [W/m ²]	736 / 288



Innlights^{TC}

Displaysolutions

InnScreen C3

PHYSICAL FACTS

ANGLE ADJUSTMENT [deg]	- 20 / + 30
PIXEL PITCH [mm]	3,91
BRIGHTNESS [cd/m ²]	1.200
PROTECTION LEVEL [Front/Back]	IP 43
CABINET WEIGHT [kg]	9
CABINET SIZE [mm]	500 x 500 x 75
CABINET RESOLUTION [px]	128 x 128
PIXEL DENSITY [px/m ²]	65.536
CABINET MATERIAL	Aluminum CNC finish

ACCESSORIES

CABINET CASE SIZE (LxWxH) [cm]	105 x 58 x 75
CABINET CASE WEIGHT (full) [kg]	114
CABINETS PER CASE	8
m ² PER CASE	2
HANGING BRACKETS	Single / Double

EASYFRAME-SYSTEM FOR STACKED INSTALLATIONS

INNLIGHTS STANDARDS

Black Face LED (Indoor Series)
Professional Image Processing / Video Direction
Certificates: CE (EMV), RoHs

OPTICAL FACTS

VIEWING ANGLE HOR/VER [Deg]	140 / 140
REFRESH RATE MIN. [Hz]	1.920
IC DRIVER	MBI 5124
LED TYPE	SMD 2121 (black face)
LED	Kinglight
PROCESSING [bit]	16
VIDEO PROCESSING	Novastar

POWER SUPPLY

INPUT VOLTAGE [V]	110 - 220
WATTAGE MAX./AVG. [W /Cabinet]	184 / 72
WATTAGE MAX./AVG. [W /m ²]	736 / 288
CABINETS PER 16 A PHASE	16

ENVIRONMENT

OPERATION HUMIDITY [RH]	10% - 90%
WORKING TEMP. MIN./MAX. [°C]	-30 / +40