



Innlights^{TC}
Displaysolutions

InnScreen F10

[PIXEL PITCH 10 mm] Outdoor

// Fixed-Installation Outdoor

All weather & UV resistance
combined with high brightness.

Sealed cabinet design and full front & rear access
define the F-Series as the prime selection for
permanent outdoor installations.

4 cabinet sizes available.



FACTS [m²]

BRIGHTNESS [cd/m ²]	6.000
WEIGHT [kg/m ²]	30
RESOLUTION [pixel/m ²]	100 x 100
WATTAGE MAX./AVG. [W/m ²]	625 / 250


InnScreen F10 // Customized

PHYSICAL FACTS

PIXEL PITCH [mm]	10
BRIGHTNESS [cd/m ²]	6.000
PROTECTION LEVEL [Front/Back]	IP 65 / IP 54
PIXEL DENSITY [px/m ²]	10.000
CABINET MATERIAL	Aluminum sheet
CABINET DEPTH [mm]	86

4 CABINET SIZES [mm]

800 x 800 | 1.200 x 1.200 | 800 x 1.200 | 1.200 x 800



OPTICAL FACTS

VIEWING ANGLE HOR/VER [Deg]	140 / 20 (up) 60 (down)
REFRESH RATE MIN. [Hz]	1.920
IC DRIVER	MBI 5153
LED TYPE	Nationstar SMD 3535
PROCESSING [bit]	14
VIDEO PROCESSING	Novastar

POWER SUPPLY

INPUT VOLTAGE [V]	110 - 220
WATTAGE MAX./AVG. [W /m ²]	625 / 250

ENVIRONMENT

OPERATION HUMIDITY [RH]	10% - 90%
WORKING TEMP. MIN./MAX. [°C]	-30 / +70

INNLIGHTS CUSTOMIZED

IC Driver / Refresh rate

SMD type

INNLIGHTS SYSTEM INTEGRATION

Framework Design

Digital Signage Advising & Creating

Digital Signage via Online Remote

Monitoring Solutions

Permissions Support