



Innlights^{TC}
Displaysolutions

InnScreen S2

[PIXEL PITCH 2,6 mm] Indoor

// Fixed Installation Indoor

Most reliable fixed installation cabinet
with brilliant video performance.

Light profile.

Front and rear service through magnetic
design with push & pull function.

Direct wall mounting.



FACTS [m²]

BRIGHTNESS [cd/m ²]	800
WEIGHT [kg/m ²]	24
RESOLUTION [pixel/m ²]	384 x 384
CABINETS PER m ²	4
WATTAGE MAX./AVG. [W/m ²]	536 / 216



Innlights^{TC}

Displaysolutions

InnScreen S2

PHYSICAL FACTS

PIXEL PITCH [mm]	2,604
BRIGHTNESS [cd/m ²]	800
PROTECTION LEVEL [Front/Back]	IP 20
CABINET WEIGHT [kg]	6
CABINET SIZE [mm]	1.000 x 250 x 42
CABINET RESOLUTION [px]	384 x 96
PIXEL DENSITY [px/m ²]	147.456

INNLIGHTS STANDARDS

Black Face LED (Indoor Series)

Professional Image Processing / Video Direction

Certificates: CE (EMV), RoHs

INNLIGHTS CUSTOMIZED

IC Driver / Refresh rate

SMD type

INNLIGHTS SYSTEM INTEGRATION

Framework Design

Digital Signage Advising & Creating

Digital Signage via Online Remote

Monitoring Solutions

Permissions Support

OPTICAL FACTS

VIEWING ANGLE HOR/VER [Deg]	140 / 140
REFRESH RATE MIN. [Hz]	1.920
IC DRIVER	MBI 5153
LED TYPE	SMD 2121
LED	Nationstar
PROCESSING [bit]	14
VIDEO PROCESSING	Novastar

POWER SUPPLY

INPUT VOLTAGE [V]	110 - 220
WATTAGE MAX./AVG. [W /Cabinet]	134 / 54
WATTAGE MAX./AVG. [W /m ²]	536 / 216
CABINETS PER 16 A PHASE	22